

iq.ul.com

Positioning Devices

E528767

Guide Information

**Right2Buy Inc.**

578 Kennedy Rd, Akron OH 44305-4426

**ZIP-HD-200-8+**

Nonmetallic Cable Ties Investigated to ANSI/UL 62275, CAN/CSA-C22.2 No. 62275

<u>Type</u> <u>Dsg</u>	<u>Min Bundle</u> <u>Diameter</u> <u>mm</u>	<u>Max Bundle</u> <u>Diameter</u> <u>mm</u>	<u>Loop</u> <u>Tensile Str</u> <u>N</u>	<u>Min Oper</u> <u>Temp</u> <u>°C</u>	<u>Max Oper</u> <u>Temp</u> <u>°C</u>	<u>Min Install</u> <u>Temp</u> <u>°C</u>	<u>Resistant</u> <u>to UV</u> <u>Light</u>	<u>Plenum</u> <u>Rating</u>	<u>Also Classified to</u> <sup>[^]</sup> <u>IEC 62275 and</u> <u>EN 62275</u>
21,21S	6.0	50.9	550	-40	85	-20	-	AH-2	-

+ - Product designation includes suffix "AH" to reflect AH-2 Plenum Rating.

Report Date: 2022-10-12

Last Revised: 2022-10-13

© 2022 UL Solutions

