



- Self-locking head design speeds installation and locks into place at any length along tie body
- Provides a strong, durable method of cable bundling
- Can be used in a wide range of indoor, outdoor, and underground (including direct burial)
- Smooth surfaces and rounded edges assures cable protection and worker safety
- Provide the ultimate support for network cables
- Material:
 - 304 stainless steel for general-purpose applications
 - 316L stainless steel for the most corrosive environments
- Working (Operation) Temperature: -80°C - + 538°C (-112°F - + 1000°F)
- Min Installation Temperature: -60°C (-76°F)
- Any Length is available
- Water absorption: none
- Flammability: non-flammable
- Ultraviolet resistance: excellent,
- Chemical resistance: excellent
- UL (Underwriters Laboratories) :
File E258930 based
newest standard UL62275

Tolerance unspecified
mm (inch)
X.XXX ±0.1 (0.004)
X.XX ±0.25 (0.010)
X.X ±0.5 (0.02)
X. ±1.0 (0.04)
ANGULAR ± 2°



Item No.	Size(mm)	L	W	T	Min Bundle Diameter	Max Bundle Diameter	Tensile Strength
222122	7.9x360	360	7.9	0.25	15.0	112.8	1600N(350lb)
222126	7.9x680	680	7.9	0.25	15.0	214.8	1600N(350lb)